

## in der Bank Austria Halle Gasometer

## **Technical Information Sheet**

(last update: OKT - 2020)

# **Index**

- 1. PA
- 2. FOH
- 3. Monitoring
- 4. Cabling / Mics
- 5. Stage/ Backline / Power
- 6. Loading

For any question about this document please don't hesitate to get in contact via email! I'm always happy to talk to people on the phone in advance as long as we have an appointment, so everybody is prepared and we can sort things out real quick and easy!

DI (FH) Robert Breunhölder
Technical Venue Manager
Guglgasse 8,
1110 Wien
robert@planet.tt



#### 1. PA

- 08 x L-Acoustics Kudo / Side flown
- 08 x L-Acoustics SB218
- 04 x Martin Audio EM25 Nearfills (Mono)
- 02 x Martin Audio EM25 Outfills (Mono)

#### Processing:

- 01 x EV NetMax N8000 (Analalog 16in / 16 out)
- 10 x LAB-Gruppen FP10000Q Amps

For sold out shows or Music with lots of Bass it is highly recommended to use 4 additional SB218 Subs, which can easily be integrated into the existing setup. Additional Subs are not available in house, but can be rented from one of our partners at low cost.

#### 2. FOH

- 01 x Midas H3000 44+4
- 02 x Midas H3000 PSU

#### Siderack FX:

- 01 x TC D Two
- 01 x Lexicon PCM 70
- 01 x Yamaha SPX 990
- 01 x Yamaha SPX 2000
- 01 x TC M2000
- 01 x Lexicon PCM 80
- 01 x CD/Tape
- 01 x Siderack Inserts: 02 x BSS DPR 504 Quadgate
- 02 x BSS DPR 404 Quadcompressor
- 04 x dbx 160A Monocompressor
- 01 x XTA GQ 600 (Dual 31Band Graphic EQ)

#### 3. Monitoring

- 01 x Allen & Heath dLive S5000
- 01 x Allen & Heath DM64 Stagebox
- 06 x L-Acoustics 115FM on 6 CH Floor Wedge Control (incl. CUE Wedge)
- 02 x Sidefills: 01 x RCF TTP 5-A (Active 15"+2", 1600W)
  - 01 x RCF TTS 26-A (Active Sub, 2x15", 3400W)
- 01 x Drumfill: 01 x Meyer Sound CQ1 Top (Active 15"+4", 1240W)
  - 01 x Meyer Sound 650P Sub (Active Sub, 2x18", 1240W)



## 4. Cabling / Mics

- 48 Channel BSS active Splitter
- 06 x Subcoresystem LK37 12Channel Inputbox
- 01 x Patchbay 4 x LK37 in 48 x XLR out
- 01 x Multicoresystem LK37 36 Channel send to FOH 60m
- 01 x MuticoreSystem LK37 36 Channel send to Monitor 1,5m

#### Misc.:

Microphones/DI's:

Standardsets of Shure, Sennheiser, AKG, Audix (List on request)

### 5. Stage/ Backline / Power

Standard Stage size: 16 x 8 x 1,5m

Clearance: 6m

SL Wing (Monitor): 2 x 3m

Stairs SL

#### Backline:

We don't have any Backline in house!

#### **Backline - Power:**

3 x 16A CEE 1PH or Schuko Type.

### 6. Loading

The loading Dock on ground level holds one Truck. Distance to Stage: 20m (even with the ground)

